

1.5C-2V 75Ω



Construction:

- **Inner Conductor** : solid copper, diameter 0.26 mm
- **Insulation (dielectric)**: Solid polyethylene, external Diameter 1.6mm
- **External conductor**: Copper wires braid, 95% optical covering
- **Sheath**: PVC, external diameter $2.9 \pm 0,2$ mm
- **sheath colour**: black

Technical Data :

Temperature range:

- during installation: -15 °C up to +55 °C
- operating temp.: -40 °C up to +85 °C

Min. inner bending radius:

- without load: 5D (15 mm)
- under load: 10D (30 mm)

Behavior in fire: IEC 60332-1

Maximal tensile strength: 75 N

Cable weight: 14 kg/km

Design Standard

JIS - C- 3501

Electrical Data:

Conductor DC Resistance @20°C		[Ω/km]	968
Insulation resistance		[MΩ/km]	>10000
Impedence	ZL	[Ohm]	75 +/-3
Attenuation	200 MHz	[dB / Km]	393
Capacitance	C	[PF/m]	69+/-4
Rel. velocity ratio	V rel	%	85
Test voltage		[kV]	1.0

Application:

Radio Applications Interior lines for communication, Wireless equipment for personal radio, MCA, AVM, and amateur radio, Antenna feeder line, Wiring between or inside high frequency transmission units.

Frequency MHz	Attenuation at 20 °C dB/100m
1	2.7
10	9.6
30	14.3
200	39

