

2.5D-2V 50Ω



Construction:

- **Inner Conductor** : solid copper, diameter 0.8 mm
- **Insulation (dielectric)**: Solid polyethylene, external Diameter 2.7mm
- **External conductor**: Copper wires braid, 75% optical covering
- **Sheath**: PVC, external diameter $4.38 \pm 0,2$ mm
- **sheath colour**: black

Technical Data :

Temperature range:

- during installation: -15 °C up to +55 °C
- operating temp.: -40 °C up to +85 °C

Min. inner bending radius:

- without load: 5D (22 mm)
- under load: 10D (44 mm)

Behavior in fire: IEC 60332-1

Maximal tensile strength: 80 N

Cable weight: 31 kg/km

Design Standard

JIS - C- 3501

Electrical Data:

Conductor DC Resistance @20°C		[Ω/km]	110
Insulation resistance		[MΩ/km]	>1000
Impedence	ZL	[Ohm]	50 +/-3
Attenuation	10 MHz	[dB / Km]	85
Capacitance	C	[PF/m]	104+/-4
Rel. velocity ratio	V rel	%	85
Test voltage		[kV]	1.0

Application:

Radio Applications Interior lines for communication, Wireless equipment for personal radio, MCA, AVM, and amateur radio, Antenna feeder line, Wiring between or inside high frequency transmission units.

Frequency	Attenuation at 20 °C
MHz	dB/Km
1	22
10	85
30	142
200	385

