


AV-V (5-100)

CU/PVC



PVC Insulated, Non Sheathed cable for Automotive (Battery Cable)

Construction

Conductor: Copper conductor fine wire stranded as per DIN ISO 6722 part 3 .

Insulation: Soft-PVC with properties according to ISO 6722-1, Type T1

Insulation colour: ● Black, ● Blue, ● Orange, ● Red, ○ White
Other colours available upon request

Abbreviations

A : low-tension cable for automobiles

V : Vinyl Insulated

V : Vibration Type

Properties :

- Oil and fuel resistant as per DIN ISO 6722 part 2

Technical data

Temperature range:

Max Working Temperature :	+80 °C
Min Working Temperature :	- 40 °C
Hot-pressure resistance test at:	+120 °C

Nominal voltage:

25V AC - 60V DC

Test voltage:

3kv i.e < 0.5mm²
5kv i.e > 0.5mm²

Minimal inner bending radius:

single core :8 x D

Withstand Voltage test :

Spark :5000V for 15sec
Immersion :1000V for 1Min

DESIGN STANDARDS

KS C 3311

ISO 6722

JASOD 611

APPLICATION

- Cable used in low voltage circuits in automobiles (Battery Cable)

AV-V (5-100)

CU/PVC

Nominal size (mm ²)	Construction (No/mm)	Calculated area (mm ²)	Outer diameter (mm)	Thickness (mm)	Overall diameter Standard (mm)	Overall diameter Max (mm)	Conductor resistance (Ω/Km)	Current limit (A)	Approx. weight (g/m)	Standard length (m)
5	63/0.32	5.066	3.1	0.8	4.7	5.0	3.58	51	6.5	1,500
8	105/0.32	8.444	4.1	1.0	6.1	6.4	2.14	66	6.0	1,500
10	114/0.32	9.168	4.2	1.0	6.2	6.5	1.96	82	8.5	1,000
15	171/0.32	13.75	5.3	1.0	7.3	7.8	1.32	92	8.0	1,000
20	247/0.32	19.86	6.3	1.0	8.3	8.8	0.915	121	11.0	800
30	361/0.32	29.03	7.8	1.0	9.8	10.3	0.625	168	12.0	800
50	608/0.32	48.89	10.1	1.0	12.1	12.8	0.371	220	16.5	600
60	741/0.32	59.59	11.1	1.4	13.9	14.6	0.304	243	16.0	600
85	1064/0.32	85.57	13.1	1.4	15.9	16.6	0.212	300	24.5	500
100	369/0.32	110.10	15.1	1.4	17.9	18.8	0.165	356	23.5	500

Insulation materials for the production of automotive cables

Service temperatures			Resistance to								
Temperature index	Thermal overload capacity	Cold winding test	Specific volume resistance	Abrasion	Flame retardance	Oil	Fuels	Brake fluid	Acids/alkalis	Organic agents	
ISO 6722-1 oder ISO 14572			IEC 93 DIN 53482	ISO 6722-1 oder ISO 14572							
°C/3,000 h	°C/48 h	°C	Ω · cm								
100/105	125	-40	>10 ¹²	+	+	+	+	-	+	-	
105	110	-50	>10 ¹²	+	+	+	+	-	+	-	
125	140	-40	>10 ¹²	+	+	+	+	-	+	-	
90	100	-40	>10 ¹⁶	+	--	-	+	--	+	-	
105	140	-40	>10 ¹²	++	-	++	++	+	+	+	
125	150	-40	>10 ¹⁶	+	--	+	+	-	+	+	
125	150	-40	>10 ¹⁴	+	+	+	+	-	+	+	
°C/3,000 h	°C/48 h	°C	Ω · cm								
110/125	150	-40	>10 ⁹	++	+	++	++	+	+	+	
90	150	-40	>10 ⁹	++	-	++	++	+	-	+	
150	180	-40	>10 ⁹	++	+	++	++	+	+	+	
125	150	-40	>10 ¹⁰	-	+	+	+	-	+	-	
90	120	-40	>10 ¹⁰	++	-	++	++	+	-	+	
125	150	-40	>10 ¹⁴	-	+/-*	-	-	-	+	-	
°C/3,000 h	°C/48 h	°C	Ω · cm								
200	225	-80	>10 ¹⁶	-	+	+	+	++	+	+	
140	180	-40	>10 ¹⁰	-	-	-	-	-	-	-	
105	140	-40	>10 ¹²	++	+	+	+	-	+	+	
125-150	150	-40	>10 ¹⁴	+	+	+	+	-	+	+	
°C/3,000 h	°C/48 h	°C	Ω · cm								
260	305	-90	>10 ¹⁸	++	++	++	++	++	++	++	
210	260	-65	>10 ¹³	++	++	++	++	++	++	++	
180	230	-65	>10 ¹³	++	++	++	++	++	++	++	
150	160	-30	>10 ¹⁴	++	++	++	++	++	+	+	
260	290	-90	>10 ¹³	++	++	++	++	++	++	++	

++ excellent + good - fair -- poor

* depending on the recipe, on demand